

MARTIN POWER
MP 625 O
BASE GENSET



Output Ratings

Prime power - PRP	632 kVA / 506 kW
Standby power - ESP	700 kVA / 560 kW
Current	912 A
Voltage	400 V / 230 V
Frequency	50 Hz
Voltage system	TN-C

Prime power

These ratings are applicable for supplying continuous electrical power. There is no limitation to the hours of operation and this model can supply 10% overload power for 1 hour in 6 hours

Standby power

These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. In this rating max 500 hours per year is allowed with maximum continuous work for 300 hours

Basic informations

Engine brand	VOLVO
Engine model	TWD1643GE
Emmissions limit	stage II
Speed	1500 min-1
Control panel current	- / 1000 A / 1000 A
AMF1 / AMF5 ,M1 ,P1 / ATS	
Standard fuel tank capacity	1000 l


Dimmensions and weights

Length (L)	TBD
Width (W)	TBD
Height (H)	TBD
Height with CP*(HCP)	TBD
Weight without CP*	TBD

* Control panel

Available alternators

Meccalte	ECO40-2L/4
Sincro	SK 355 LM
Marelli	MJB 355 MA 4
Weg	315MI20AI



- TBD - To be defined later
- All pictures are for informational purposes only
- We reserve the right to change the specification without notice

Genset details

Consumption at PRP	124,9 l
Consumption at 75 % of PRP	92,3 l
Consumption at 50 % of PRP	61,5 l
Consumption at 25 % of PRP	33,7 l
Battery voltage	24 V
Battery	2 x 140 Ah

Standard scope of supply

Engine	
4 stroke diesel engine	
Engine harness	
Radiator with fan	
Air filter	
Intercooler	
Turbocharger (for turbocharged engines)	
Charging alternator	
Oil cooler	
Oil filter	
Fuel filter	
Fuel supply pump	
Oil draining valve	
Starter	
Alternator	
Self regulation system	
Self excitation system	
Synchronous	
Single bearing	
Protection IP 21	
Automatic voltage regulator	
Brushless	
Flexible connection disk + housing	
Base frame	
Steel base frame	
Flexible antivibration mounting	
Integrated fuel tank	
Fuel level sensor	
Fuel filling cap with ventilation	
Starting accumulator	
Counter flange,sealing,set of coonection material	
Initial filling of oil and coolant	
Standard factory load test	
Operation and maintenance manual	

Engine details

Prime power - PRP	536 kW
Standby power - ESP	596 kW
Intake	turbocharged with intercooler
Speed governor	electronic
Cylinders	6L
Displacement	16,12 dm3
Air requirements for intake	44 m3/min
Air requirements for cooling	590 m3/min
Max. back pressure at intake	5 kPa
Thermic power - cooling	366 kW
Thermic power - irradiated	53 kW
Exhaust gas flow	101,6 m3/min
Max. back pressure at exhaust	10 kPa
Max. exhaust temperature	450 °C
Performance class	TBD
Specific fuel consumption	199 g/kWh
Engine oil volume	48 l
Coolant volume	166 l

Available additions

Control panel	MP Manual MP Automatic MP Parallel MP ATS
Canopy	95 LWA (70dB/7m) 90 LWA (65dB/7m)
Container	TBD
Industrial exhaust silencer -20 dB	DN 200
Residential exhaust silencer -30dB	DN 200

Basic options

Retention bath	
Increased fuel tank	3000 l
Increased IP Protection	
Front air output for canopy	
Electronic speed governor	
Homologized chassis for road transport	
Separate storage tank	
Automatic fuel filling device (AFD)	

Lot more options available

Canopy - 95 LWA (70 dB at 7 m)

Side and back doors with lockers

Side and/or back air inlet with jalousies

Top air outlet

Possition of exhaust silencer in canopy

Red (RAL3000) + Black (RAL9005) color of canopy

Length (L) 4925 mm



Width (W) 2250 mm

Height (H) 2695 mm

Height with industr. silencer (HI) -

Height with resid. silencer(HR) -

Weight without control panel and exhaust silencer TBD



Canopy - 90 LWA (65 dB at 7 m)

Side and back doors with lockers

Side and/or back air inlet with jalousies

Top / side air outlet

Red (RAL3000) + Black (RAL9005) color of canopy

Retention bath


Exhaust silencer inside of canopy

Length (L) TBD

Width (W) TBD

Height (H) TBD

Weight without control panel and exhaust silencer TBD



- TBD - To be defined later
- All pictures are for informational purposes only
- We reserve the right to change the specification without notice