

## MARTIN POWER MP 60 I



### Output ratings

Prime power - PRP	60 kVA / 48 kW
Standby power - ESP	66 kVA / 53 kW
Current	87 A
Voltage	400 V / 230 V
Frequency	50 Hz
Voltage system	TN-S

#### Prime power - PRP

These ratings are applicable for supplying continuous electrical power. There is no limitation to the hours of operation and this model can supply 10% overload power for 1 hour in 6 hours.

#### Standby power - ESP

These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. Maximum 500 operating hours per year are allowed with maximum continuous work for 300 hours.

### Basic information

Engine brand	FPT - IVECO
Engine model	N45 SM1A
Emission limit	stage II
Speed	1500 min-1
Control panel current	100 A (100 A)
AMF5, M1, P1 (AMF1)	
Standard fuel tank capacity	200 l


### Dimensions and weights

Length (L)	2265 mm
Width (W)	1112 mm
Height (H)	1301 mm
Height with CP* (HCP)	1578 mm
Weight without CP*	929 kg

\* Control panel

### Available alternators

Mecc Alte	ECP32-2M/4
Sincro	SK 225 SM
Marelli	MJB 200 MA 4
WEG	GTA 201 AIHB



- TBD - To be defined later
- All pictures are for informational purposes only
- We reserve the right to change the specification without notice

#### Genset details

Consumption @ 100% PRP	13,6 l
Consumption @ 75 % of PRP	10,2 l
Consumption @ 50 % of PRP	7,2 l
Consumption @ 25 % of PRP	4,2 l
Battery voltage	12 V
Battery	88 Ah

#### Standard scope of supply

Engine
4-stroke diesel engine
Engine harness
Radiator with fan
Air filter
Intercooler
Turbocharger (for turbocharged)
Charging alternator
Oil cooler
Oil filter
Fuel filter
Fuel supply pump
Oil draining valve
Starter
Alternator
Self regulation system
Self excitation system
Synchronous
Single bearing
Protection IP 21
Automatic voltage regulator
Brushless
Flexible connection disk + housing
Base frame
Steel base frame
Flexible antivibration mounting
Integrated fuel tank
Fuel level sensor
Fuel filling cap with ventilation
Starting accumulator
Counter flange, sealing, set of connection material
Initial filling of oil and coolant
Standard factory load test
Operation and maintenance manual

#### Engine details

Prime power - PRP	53,3 kW
Standby power - ESP	59 kW
Intake	turbocharged
Speed governor	mechanical
Cylinders	4L
Displacement	4,5 dm <sup>3</sup>
Air requirement for intake	6,3 m <sup>3</sup> /min
Air requirement for cooling	90 m <sup>3</sup> /min
Max. back-pressure at intake	5 kPa
Thermal power - cooling	30 kW
Thermal power - radiated	16 kW
Exhaust gas flow	11 m <sup>3</sup> /min
Max. back-pressure at exhaust	5 kPa
Max. exhaust temperature	483 °C
Performance class	G 2
Specific fuel consumption	211 g/kWh
Engine oil volume	13 l
Coolant volume	19 l

#### Available options

Control panel	MP Manual MP Automatic MP Parallel MP ATS
Canopy 95LWA type [LWA / dB(A)]	93 / 68 @ 7 m
Canopy 90LWA type [LWA / dB(A)]	90 / 65 @ 7 m
Container	10'
Industrial exhaust silencer -20 dB	DN 70
Residential exhaust silencer -30 dB	DN 70

#### Basic options

Retention bath	
Increased fuel tank	500 l
Increased IP Protection	
Front air output for canopy	
Electronic speed governor	
Homologized chassis for road transport	
Separate storage tank	
Automatic fuel filling device (AFD)	

Many more other options available

## Canopy - type 95 LWA

Side and back doors with lockers

Side and/or back air inlet with jalousies

Top air outlet

Position of exhaust silencer in the canopy

Canopy colour: top RAL 3000 / bottom RAL 9005

Length (L) 2700 mm



Width (W) 1112 mm

Height (H) 1890 mm

Height with industr. silencer (HI) -

Height with resid. silencer (HR) -

Weight without control panel and exhaust silencer 1379 kg



## Canopy - type 90 LWA

Side and back doors with lockers

Side and/or back air inlet with jalousies

Top / side air outlet

Canopy colour: top RAL 3000 / bottom RAL 9005

Retention bath



Exhaust silencer inside of canopy

Length (L) 3065 mm

Width (W) 900 mm

Height (H) 1630 mm

Weight without control panel and exhaust silencer 1345 kg



- TBD - To be defined later

- All pictures are for informational purposes only

- We reserve the right to change the specification without notice

TTS Martin, s.r.o.

038 42 Pribovce 343, Slovakia

Tel.: +421 / 43 / 429 44 66